



AT-8000S/16

Layer 2 Managed Fast Ethernet Switch

AT-8000S/16

16-port standalone 10/100TX L2 switch with 1 active SFP bay (unpopulated) and 1 standby 10/100/1000T ports (RJ-45)

Overview

The small form factor AT-8000S/16 provides line-rate Layer 2 switching in an affordable, fixed-configuration platform. Featuring easy installation and exceptional reliability, this 10/100 switch comes with one gigabit uplink port with the option of the integrated Copper 10/100/1000 port or a 100 or 1000 SFP slot for fiber connectivity.

Ideal Workgroup and Remote Office Connectivity

Designed for the smaller workgroup or remote office this highly featured switch mirrors the advanced feature set of the larger 8000S stackable products while offering the benefits of silent operation and a port density aimed at small networks.

Easy Access Networking

Featuring an industry standard CLI and Allied Telesis' intuitive WEB interface the advanced features of the 8000S/16 are accessible to a wide range of system administrators. The well known CLI and WEB interfaces significantly reduce learning time and minimize the cost of deployment.

Secure Management

Only authorized administrators can access the management interface of the AT-8000S series. Protocols such as SSL, SSH and SNMP v3 facilitate this protection of your network with local or remote connections.

Securing the Network Edge

To ensure the protection of your data, it is important to control access to your network. Protocols such as 802.1x port based authentication guarantee that only known users are connected to the network. Unknown users who physically connect can be isolated to a pre-determined part of your network offering guests such benefits as Internet access while ensuring the integrity of your private network data.

Key Features

Easy, Well Known Management

- Industry Standard CLI
- Simple intuitive, full features Allied Telesis Web Interface
- Secure encrypted WEB and CLI management with SSH v2 and SSL
- SNMP

All the QoS Needed in the Wiring Closet for Today's Voice and Data Networking

- 8 Priorities assigned to 4 queues
- 802.1p for Layer 2 QoS
- DSCP (Diffserv) for Layer 3 QoS
- 802.1p to DSCP remarking traffic ready for transport to the Layer 3 core of the network

Securing the Network at its Most Vulnerable Point

- 802.1x and RADIUS network login: *for advanced control of user authentication and accountability*
- Guest VLAN: *to ensure visitors or unauthorized users connect only to services defined by IT. E.g. Internet*
- TACACS+: *for ease of management security administration*

Small Form Factor

- Standalone switch for remote locations or where stacking is not required
- Silent operation (fanless)

AT-8000S/I6 | Layer 2 Managed Fast Ethernet Switch

System Configuration

W x D x H	330mm x 230.5mm x 43.2mm (12.99" x 9.07" x 1.73")
Weight	1.95kg (4.29lb)
Mounting	19" rack-mountable hardware included

System Capacity

64MB RAM
16MB Flash Memory
400Mhz CPU
Up to 4,096 VLAN ID
8,000 MAC address

Performance

Wire speed switching on all Ethernet ports
14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps fast Ethernet
1,488,000pps for 1000Mbps Gigabit Ethernet

Ethernet throughput:	3.9Mpps
Chipset switching capacity	5.2Gbps
MTBF	447,901.90 Hours

Store and forward mode
Non blocking switch fabric
Auto-MDI/MDI-X

Port speed:	
10/100-TX	RJ-45
10/100/1000TX	RJ-45
100-FX, 1000-SX, 1000-LX	SFP slot
RS232	DB9 pin, male port
Internal power supply	— no fan

Interface Standards

802.3	10Base-T & 10Base-FL
802.3u	100Base-TX & 100base-FX
802.3z	1000base-SX
802.3ab	1000Base-T

General Standards

802.1d	Bridging
802.3x	BackPressure/ Flow Control

Redundancy Standards

802.1D	Spanning Tree Protocol
802.1W	Rapid Spanning Tree
802.1s	Multiple Spanning Tree
802.3ad	LACP Link Aggregation (with up to 8 members per group and up to 8 groups per device)

Static port trunk

Quality of Services (QoS)

QoS in layer 2 (802.1p compliant Class of Service)
Traffic prioritization using 802.1p, ToS, DSCP fields
Map 802.1p priorities to CoS queues to prioritize traffic at Egress.
Strict Scheduling and Weighted Round Robin

VLANs

IEEE 802.1Q VLAN Tagging
Up to 256 VLANs
Port-based VLANs
MAC-based VLANs
Private VLANs
GARP VLAN Registration Protocol (GVRP)
IEEE 802.3ac

Multicast Standards

RFC1112	IGMP snooping (ver. 1)
RFC2236	IGMP snooping (ver. 2)
RFC 3376	IGMP snooping (ver.3)*

* Future Release

Management and Monitoring

WEB, CLI, Serial	
RFC 1157	SNMPv1/v2c
RFC 2570	SNMPv3
RFC1213	MIB-II
RFC 1215	TRAP MIB
RFC1493	Bridge MIB
RFC 2863	Interfaces group MIB
RFC 1643	Ethernet like MIB
RFC 1757	RMON 4 groups: Stats, History, Alarms, Events
RFC 2674	802.1Q MIB
RFC 1866	HTML
RFC 2068	HTTP
RFC 854	Telnet
RFC 783	TFTP

IP address allocation
RFC 951/ RFC 1542 BootP / DHCP
Manual

RFC 2030 SNMP (Simple Network Time Protocol)
Syslog Event
Dual Software Images

Security

Management Security: user name
and password protection
SSHv2 Telnet management
SSLv3 WEB management
RFC 1492 TACACS+
RFC 2138 RADIUS Authentication
IEEE 802.1x Port-based network access control
Guest VLANs

Fault Protection

Broadcast Storm Control

AT-8000S/16 | Layer 2 Managed Fast Ethernet Switch

Power Characteristics

Voltage input	100- 240VAC
Voltage output	12VDC
Current	1.5A
Power consumption	30W
Heat dissipation	102.45BTU/hour
Clock Frequency	166MHz

Environmental Specifications

Operating Temp	0°C to 45°C (32F to 113F)
Storage Temp	-25°C to 70°C (-13F to 158F)
Relative Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Operating Altitude	maximum 3,000m (9,843ft)

Electrical/ Mechanical Approvals

Safety	UL 1950 (UL/cUL), EN60950 (TUV)
EMI	FCC Class A, EN55022 Class A, VCCI Class A, C-Tick, EN61000-3-2, EN61000-3-3
Immunity	EN55024
RoHS	compliant

Package Description

One AT-8000S/16 switch
Power cord AC
Rackmount kit
Rubber feet for desktop installation
RS232 management cable
Install guide and user guide in CD
Limited Lifetime warranty card

Country of Origin

China

Ordering Information

AT-8000S/16-xx

16-port standalone 10/100TX L2 switch with 1 active SFP bay (unpopulated) and 1 standby 10/100/1000T ports (RJ-45)

Where xx = 10 for U.S. power cord
20 for no power cord
30 for U.K. power cord
40 for Australia power cord
50 for Europe power cord

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000174 Rev.D